

FIRE-RESCUE - SAFETY CATALOG



MYANMAR



VIETNAM



THAILAND



COMBODIA



MALAYSIA



BRUNEI DARUSSALAM



RESCUE




FIRE



Devcon

EIS



SAFETY

MRO

ABRASIVE

ADHESIVE



PACIFIC AND FIRE AEC Co., Ltd.

Tel. 0-2038-5840-41 Fax. 0-2886-7585 www.pacificandfire.com

WARRANTY

PACIFIC AND FIRE AEC Co., Ltd. WARRANTY TERMS

WHAT IS PROTECTED: Pacific and Fire AEC Co., Ltd. (Seller) provides a LIMITED one year warranty on all products sold by the company. The agreement is between the Seller and the Purchaser. The one (1) year warranty begins on the day the tax invoice is issued and continues for 365 days. The warranty is valid when the item purchased is used correctly, for the intended purpose and application, stored and maintained according to the owner's manual and used in a safe manner by trained persons. If there is any question regarding the use, maintenance, storage or safe practice when using any of the products sold by Pacific and Fire AEC Co., Ltd., please contact the seller to provide any information the user may require.

EXCLUSIONS: The Limited One Year Warranty covers all defects in material and workmanship with the following exceptions, specied as follows: (1) damage or failure due to accident, neglect in maintenance, unsafe or incorrect use in the wrong application, normal wear and tear, mishandling, damage from improper storage. Repairs or modifications from any person other than the trained technician at Pacific and Fire AEC Co., Ltd., voids the warranty.

WARRANTY CLAIMS: When a warranty claim is submitted, the defective goods must be returned to Pacific and Fire AEC Co., Ltd. for inspection. Once the goods are received, the goods will be inspected to determine the cause of the defect. Once the cause is determined, a reply will be provided to the purchaser as to the cause and whether the defect is covered by the warranty or falls under the "exclusion" clause.

1. If the item defect is covered by the warranty, by the decisn of Pacific and Fire AEC Co, Ltd., the item can be repaired or replaced as may be fitting to the nature of the defect.
2. If the defect is not covered by the warranty, Pacific and Fire AEC Co., Ltd. will supply supporting information and offer to repair or replace the item as the standard repair or replacement cost.

WHO PAYS FOR WHAT: Pacific and Fire AEC Co., Ltd. will collect the item and return it to the company for inspection at no charge. If the item is located outside of the Bangkok Metropolitan Area, the purchaser will return the item to Pacific and Fire AEC Co., Ltd. at their own expense.


REPAIR: Pacific and Fire AEC Co., Ltd., offers repairs on all items that can be repaired that are distributed and sold by the company. The procedure to repair is that the item is returned to Pacific and Fire AEC Co., Ltd. for inspection and quotation on the repair. There is a thb. 500 inspection charge on most items. For Breathing Air Compressors the inspection charge is thb 5,000. The inspection charge will be included in the amount of the repair if the repair is made. If the decision is made not to repair, the inspection charge will be collected in cash with the return of the item.



CENTURY SERIES FIRE FIGHTING SUITS TO EN 469



RS CENTURY



Integrated Sit Harness

FIRE/RESCUE SUIT COMPLETE WITH INTEGRATED SIT HARNESS

- Coat, Trousers, Integrated Sit Harness, Helmet, Boots and Gloves. Sizes available M-XL
- Coat Manufactured with Integrated Hood and D-Ring and strap Connected to Sit-Harness
- Coat Has Four (4) Utility Pockets and one (1) Radio Pocket
- Trousers Constructed With H-D Adjustable Suspenders and Integrated Sit Harness. One (1) Side Pocket, Each Leg.
- 2 in.-3M Lime-Yellow/Silver Triple Trim on Coat and Trousers
- Two-layer Closure, Zipper Inner and Velcro Outer Closure, Coat and Trouser

3 LAYER CONSTRUCTION


- Outer Layer 240 gr. NOMEX ADVANCE 60/40
- Integrated and Removable Moisture and Thermal Barrier
- Breathable Moisture Barrier Material: PTFE/NOMEX
- Thermal Barrier: NOMEX Facecloth and Aramid Batt.
- Complete Suit weights less than 9 KGS.
- Manufactured to EN 469:2007 CE 0197 and ISO 9002



RS CENTURY
(MAHERO 06112)



FS CENTURY



DRD (Drag Rescue Device)



FIRE SUIT COMPLETE WITH INTEGRATED OUTER HOOD

- Coat With Integrated Hood, Trousers, Helmet, Boots and Gloves. Sizes available M-XL
- Coat Manufactured with Integrated Hood. Coat Length 95 cm. (approx.)
- Coat Has Four (4) Utility Pockets and one (1) Radio Pocket
- Trousers Constructed With H-D Adjustable Suspenders and One (1) Side Pocket, Each Leg.
- 2 in.-3M Lime-Yellow/Silver Triple Trim on Coat and Trousers
- Two-layer Closure, Zipper Inner and Velcro Outer Closure, Coat and Trouser

3 LAYER CONSTRUCTION

- Outer Layer 240 gr. NOMEX ADVANCE 60/40
- Integrated and Removable Moisture and Thermal Barrier
- Breathable Moisture Barrier Material: PTFE/NOMEX
- Thermal Barrier: NOMEX Facecloth and Aramid Batt.
- Complete Suit weights less than 8 KGS.
- Manufactured to EN 469:2007 CE 0197 and ISO 9002

NEW FEATURES

CENTURY SERIES NEW FEATURES

- AVAILABLE COLORS, ORANGE AND YELLOW
- DRD (DRAG RESCUE DEVICE) INTEGRATED IN COAT
- KEVLAR PADDED AND REMOVABLE KNEE PADS
- REINFORCED LEATHER CUFFS, COAT AND PANTS
- TAB ADJUSTMENT ON COAT CUFFS AND WAIST



**LIGHT WEIGHT
FULL PROTECTION
HIGHEST VALUE**



**LATEST FABRICS
HIGHEST QUALITY**



EAGLE SERIES FIRE FIGHTING SUITS

EAGLE SERIES FIRE FIGHTING SUITS NFPA 1971 COMPLIANT

FIRE SUITS THAT MEET YOUR BUDGET AND FIRE PROTECTION NEEDS

- Coat, Trousers, Helmet, Boots, Gloves and Optional Hood
- Sizes available M-XL (2XL as Special Order)
- Coat Manufactured with Four (4) in. Raised Collar (Eagle II) Or Integrated Hood (Eagle I)
- Coat Has Four (4) Utility Pockets and one (1) Radio Pocket
- Trousers Constructed With H-D Adjustable Suspenders
- One (1) Side Pocket, Each Leg.
- 3 in.-3M Lime-Yellow/Silver Triple Trim on Coat and Trousers to NFPA.
- Two-layer Closure, Zipper Inner and Velcro Outer Closure, Coat and Trouser



DRD (Drag Rescue Device)



3 LAYER CONSTRUCTION

- Outer Layer 250 gr. (7.5 oz) NOMEX IIIA Shell Material
- Integrated and Removable Moisture and Thermal Barrier
- Breathable Moisture Barrier Material: PTFE/NOMEX
- Thermal Barrier: NOMEX Facecloth and Aramid Batt.
- Complete Suit weights less than 7 KGS.
- Manufactured to comply With NFPA 1971-2007 certified to EN 469:2005 CE 0362 and ISO 9002

EAGLE SERIES NEW FEATURES

- AVAILABLE COLORS, YELLOW, ORANGE, RED, NAVY
- DRD (DRAG RESCUE DEVICE) INTEGRATED IN COAT
- KEVLAR PADDED KNEES
- REINFORCED LEATHER CUFFS, COAT AND PANTS
- TAB ADJUSTMENT ON COAT CUFFS AND WAIST

STANDARD SET (as shown) : **EAGLE II** Coat and Trousers, Model **1500-2000F** Helmet, **9687L** Boots, **Euro VI** Gloves and **3018185-SF** Hood.

STANDARD SET (as shown) : **EAGLE I** Coat With Integrated Hood and Trousers, Model **1500-2000R** Helmet, **9687L** Boots, **Euro VI** Gloves and **3018185-SF** Hood.



EAGLE II
(MAHERO 08113)

EAGLE I
(MAHERO 08113)



EAGLE II With Sisor "Euro Style" Helmet and 3018285-SF PBI Hood



EAGLE II-Red With Sisor "Euro Style" Helmet and 3018285-SF PBI Hood



EAGLE II-Navy Blue With 1500-2000F Helmet and 3018185-SF PBI Hood

FIRE SUIT ACCESSORIES

FIRE SUIT STANDARD CONSTRUCTION AND SPECIAL ORDER OPTIONS

STANDARD CONSTRUCTION FEATURES



Waist Adjustment and Side Pockets on Trousers



Nomex Wristlet with Thumb Hole



Kevlar Padded Knees. Removable Kevlar Pads On Century Series.



Double Closure on Coat and Trousers

Internal Zipper and Outer Velcro Closure



Leather reinforced sleeve and pant cuffs



Three Layer Construction: Outer Shell, Moisture Barrier, Thermal Barrier



Heavy Duty Adjustable Suspenders

BSP BRAND SIZE CHART (DIMENSIONS OF COAT AND TROUER)					
SUIT SIZING (CM)	XXL	XL	L	M	S
COAT LENGTH	90	88	86	83	80
COAT CHEST SIZE	144	138	132	126	120
COAT COLLAR SIZE	54	53	52	51	50
COAT SLEEVE LENGTH	65	63	59	56	54
TROUSER WAIST SIZE	131	125	118	114	108
TROUSER LENGTH (WAIST TO CUFF)	106	104	102	101	99
TROUSER LENGTH (INSEAM)	72.5	71	70	69	67

NOTICE: SIZES STOCKED (XL ,L AND M)

SPECIAL ORDER SIZES: SMALL AND 2XL (XXL)




EAGLE II
(MAHERO 08113)



Fire Suit Equipment Bag
Included with Each Suit


SPECIAL ORDER



Shoulder Reinforcement, Reflective Trim Special Design Embroidered or Screened Logos or Names

LASERIES

CUSTOMIZED HELMETS FOR MUNICIPAL FACTORY, VOLUNTEER




VINYL NAME DECAL & D-RING

NFPA COMPLIANT
GOGGLES
OR
FACESHIELD
(NOT SHOWN)



IDENTIFIRE
PHOTOLUMINESCENT
MAGNET PANELS



MAGNET PANEL SYSTEM
& REFLECTIVE LETTERING



ESS SNAP ON/OFF OR
STANDARD ATTACHMENT KITS



NOMEX POSTMAN SLIDE,
QUICK RELEASE, OR
COMBINATION OR
LEATHER COMBINATION
CHINSTRAP




DETACHABLE 8" EARLAPS OR 11"
WILDLAND SHROUD
NOMEX & F/R COTTON



FIRE HELMETS AMERICAN NFPA STYLE

FIREFIGHTING HELMETS TO NFPA

Reliable Head Protection for Firefighting and Rescue. Model 1500-2000 (First Due) Firefighting Helmet Constructed of High Heat Resistant Thermoplastic Shell and 4.5" Heat and Scratch-resistant Face shield, Foam Impact Liner, Adjustable Chinstrap with Postman Buckle and Nomex Neck Protector. Adjustable Size Adjustment. Model TC1 Constructed of Heat and Chemical Resistant Fiberglass.



1.Outer Shell manufactured of High Temp Thermoplastic Or High Temp and Chemical Resistant Fiberglass (F500)

2.Foam Impact Liner

3.Foam Impact Liner and Fabric Liner (Model F500)

4.Woven Suspension Displaces Direct Impact

5.Heat and Scratch-resistant Face-shield (4.5"-1500-2000)

6.Adjustable Chinstrap. Postman Buckle (1500-2000)

7.Nomex Neck Protector

8.Adjustable Ratchet Suspension



1500-2000 F



MODEL BSP 1500-2000F

Firefighting Helmet

Phenix First Due PH083113-1REV.A

Manufactured to NFPA 1971-2018

& ISO 9001-2008

*Use with Eagle II Firefighting Suits



BSP 1500-2000

with Optional Google or Flashlight

MODEL BSP 1500-2000R

Fire/Rescue Helmet

Phenix First Due PH083113-1REV.A

Manufactured to NFPA 1971-2018

& ISO 9001-2008

*Use with Century Series and Eagle I Firefighting Suits

1500-2000 R



F500



MODEL F500 Economy

Fiberglass Firefighting Helmet

NFPA 1971- Compliant

*Use with Eagle II, Eagle III and Eagle IV Firefighting Suits

EURO STYLE HELMETS

SICOR "EURO" STYLE HELMETS



SICOR MODEL VFR 2009 PRO TX

Sicor Helmets Are Manufactured from High Temperature Composite (Thermoplastic and Kevlar) Shells. Lightweight 1.5 KGS.
Two-layer Eye Protection- Inner Clear Polycarbonate Goggle (Knob Adjustment)
And Large Gold-coated Polycarbonate Faceshield
Ratchet Adjustable Suspension
Padded Liner with Foam Impact Internal Cap
Two-way Adjustable Chinstrap
Manufactured to EN 443:2008. Face shield to EN 14458/2006



Helmet Attachment and Flashlight Holder for VFR 2009 Pro Tx



Helmet Attachment and Flashlight Holder for VFR 2000

SICOR MODEL VFR 2000

Sicor Helmets Are Manufactured from High Temperature Composite (Thermoplastic and Kevlar) Shells. Lightweight 1.5 KGS.
Two-layer Eye Protection- Inner Clear Polycarbonate Goggle (Pull-down)
And Large Gold-coated Polycarbonate Faceshield
Ratchet Adjustable Suspension
Padded Liner with Foam Impact Internal Cap
Two-way Adjustable Chinstrap
Manufactured to EN 443. Face shield to EN 166

AVAILABLE COLORS: WHITE, YELLOW, ORANGE AND RED



OPTIONAL FLASHLIGHTS

Choose: Pelican 3315
LED Hazardous
Location FM Approved
(3-AA Batteries Included)

Fire Suit Accessories- Hoods and Gloves

TWO-LAYER FIREFIGHTING HOODS TO NFPA 1971-2018

- Two-layer Construction Provides Excellent Heat and Flame Protection
- Non-irritating Lenzing Inner layer and Nomex or PBI outer layer
- "SF" (SURE-FIT) Models Form and Close and Comfortable Face Fit
- Manufactured in the USA
- Black Color Hoods and EN Certified Hoods Available on Request



NOMEX/LENZING

MODEL 3038185

EXTRA-LONG

BIB-CHEST LENGTH

CHEST LENGTH



NOMEX/LENZING

MODEL 3018185-SF

"BEST SELLER"



PBI/LENZING MODEL

3018285-SF

LIGHT BROWN COLOR

PBI OUTER SHELL PROVIDES
EXTRA PROTECTION.



NOMEX

MODEL 3108185

BUDGET MODEL

2-LAYER NOMEX

NFPA 70E : 2012

MODEL	COLOR	LENGTH	NFPA
3018185-SF	WHITE	18 IN.	✓
3038185	WHITE	21 IN.	✓
3018285-SF	LT.BROWN	18 IN.	✓
3108185	WHITE	15 IN.	✓

FIREFIGHTING GLOVES (Firefighting and Rescue) to NFPA and EN Standards

Made of High Quality Leather,
2-layer Kevlar Cuff,
Sizing: M, L and XL



CONSTRUCTION FEATURES:

- Fire-resistant Leather Outer Shell
- Moisture Barrier: High Quality PU (Prevents Bacterial and Steam Exposure)
- High Quality FR Batt. Thermal Barrier



Honeywell Model GL-7500

3-Layer NFPA 1971-2018
SEI Certified Model



Hysafety Model 7888

3-Layer NFPA 1971-2013
SEI Certified



BSP Model Euro VI (Mahero FG 04201)

3-Layer EN 659-2008 & CE

FIRE SUIT ACCESSORIES- FIREFIGHTING BOOTS

HARVIK FIREFIGHTING BOOTS TO EN15090 & CE and NFPA 1071-2018



HARVIK
MODEL 9687L
EN 15090 & CE
 HEIGHT: 15 in. (Approx.)
 Electrical Shock Resistant
 to 18 KV



HARVIK
MODEL 9679
NFPA 1971-2018 and UL
 HEIGHT: 16 in. (Approx.)
 Electrical Shock Resistant
 to 18 KV

Quick Donning Loops

Chemical/Oil and Heat Resistant
 Vulcanized Rubber Upper
 Flame Resistant / Hi-Vis

Heat/Flame Resistant Liner

Mdl.9679 - Kevlar

Mdl.9687L - Ceplon

Stainless Steel Midsole / Toecap

Penetration Resistant

Chemical/ Slip Resistant Sole



Shin Protection Pad
 Water-Proof



18 KV Electric Shock Resistant

FIREFIGHTING COATS **BSP FIREFIGHTING COAT 40 AND 45 INCH LENGTH**

Model BSP Eagle III 2-Layer Firefighting Coat 40 in. Length

Outer Shell: Nomex III-A
 Thermal Liner: Nomex/Aramid Batt
 3 in. Silver Reflective Trim Around Chest and Sleeves
 Two (2) Side Pockets
 NFPA 1971-2000 Compliant

Model BSP Eagle IV 4-Layer Firefighting Coat 45 in. Length

Outer Shell: Nomex III-A
 Moisture Barrier: Nomex E-89
 Thermal Liner: Nomex/Aramid Batt
 3 in. Yellow/Silver Reflective Trim on Chest and
 Sleeves (2) places

NFPA 1971-2000 Compliant

FIREFIGHTING ACCESSORIES USED WITH BSP
 EAGLE III AND EAGLE IV

- BSP 1500-2000F OR F-500 Firefighting Helmets
- Euro VI Firefighting Gloves
- Harvik 9679 (NFPA) or 9687L (EN) Firefighting Boots
- PGI 3018185-SF Firefighting Hood.



EAGLE III



EAGLE IV

FIREFIGHTING HOSE MANUFACTURED TO BS, NFPA and FM APPROVED


- Three-layer Firefighting Hose Reinforced with Woven 100 % Synthetic Fibers
- Extruded "Through the Weave" Synthetic Nitrile Rubber Inner and Outer Layer
- Smooth Bore Internal Tube, Ribbed Outer Cover For High Performance and Long Life.
- Storage Temperature to 50°C and Working Temperature to 600°C
- Excellent Chemical Resistance. Easy Maintenance, Use, Roll-up and Store.
- Each Length Marked with FM Inspection Code, Test and Compliance Certificate.



ARMTEX
ARMTEX 600 Choose From Two (2) Colors, Red and Yellow

MODEL	DIA.	WORKING PRESSURE	BURSTING PRESSURE	WEIGHT* (KG)
ARMTEX	1 1/2"	300	910	10.0
ARMTEX	1 3/4"	300	900	11.5
ARMTEX	2 1/2"	300	780	18.0
ARMTEX	3"	200	700	21.0
ARMTEX	4"	200	700	36.0
ARMTEX 600	1-1/2"	350	900	14.5
ARMTEX 600	2-1/2"	350	900	22.5

*Weight: 30m length



FIRE HOSE STANDARDS

- BURST PRESSURE- Test Performed to Burst Limit, Test Without Couplings
- ACCEPTANCE (TEST) PRESSURE- Test Performed to 66% of Burst Pressure
- WORKING SERVICE TEST PRESSURE- Test Performed with Couplings According to NFPA or BS Standard. NFPA 1961 Working Service Test Pressure for New Hose:
1.5" Diameter Hose- 300 PSI for 10 minutes
2.5" Diameter Hose- 250 PSI for 10 Minutes
4" Diameter Hose- 200 PSI for 10 Minutes


BLINDEX CLASSIFIED
UL
Approved by UL
(UNDERWRITERS LABORATORIES
INC LISTED,USA)



BLINDEX 4-LAYER FIRE HOSE (Yellow Outer Cover/Red Inner Tube)

MODEL	DIA.	WORKING PRESSURE	BURSTING PRESSURE	WEIGHT* (KG)
BLINDEX	1 1/2"	350	925	10.8
BLINDEX	2 1/2"	350	780	19.5

*Weight: 30m length



RUBBER HOSE REPAIR SYSTEM- Repair Armtex and Blindex Hoses

- Repair Holes Caused by Punctures
- Repair Tears Caused by Abrasion
- 2-Layer Vulcanized Repairs. Red and Yellow
- For Hoses 1.5" to 4". For Holes and Tears 1/8" to 2"
- After Repair, Hose Repair is Tested to 200 PSI (13.8 Bar)

EUROPE AND UNITED KINGDOM (ENGLAND) STANDARDS

- BS6391- UK STANDARD
- TYPE 1- Woven Hose
- TYPE 2- Woven and Coated Hose
- TYPE 3- Rubber Extruded Hose
- BS336- British Standard for 2.5" (64mm) Instantaneous Couplings
- TEST STANDARD: 1.5" & 2.5" (22.5 BAR FOR 1 Minute)
- EN STANDARD: EN694 and EN14510 Woven Hose
- SPANISH STANDARD: UNE
- 3RD PARTY INTERNATIONAL TESTING LABS (According to Standards)
FM, AENOR, Certied Testing Labs


WOVEN FIRE HOSE

ARMTEX HP ATTACK FIRE HOSE

- NEW DESIGN ATTACK FIRE HOSE FOR HIGH FLOW, HIGH PRESSURE REQUIREMENTS
- Double Hose Construction- Woven Outer Hose and Rubber Inner Hose
- Tough 100% Woven Synthetic Outer Jacket Improves Abrasion Resistant, Reduces Kink
- Inner Nitrile Rubber Type 3 Hose (like Armtex) Hose For Increased Water Flow
- Perfect Solution for Interior Fire Attack and Industrial and Municipal Applications


MODEL	DIA.	WORKING PRESSURE	BURSTING PRESSURE	WEIGHT
Armtex HP	1-3/4"	500 PSI	1500 PSI	16.6 KGS.*
Armtex HP	2.5"	400 PSI	1200 PSI	24.6 KGS.*

* Weight : 30 meters



WOVEN FIRE HOSE FOR USE IN BUILDINGS OR IN FIRE ATTACK

- Manufactured from 100% High Strength Synthetic Woven Yarn
- Rubber Extruded Liner Tightly Bound To Synthetic Cover
- TITAN C- Red Polyurethane Coating (DURACOAT) Increases Resistant To Chemicals, Oil and Damage from Abrasion Between 50%-70% Compared To Uncoated (White) Woven Hose



USA FIREFIGHTING EQUIPMENT STANDARDS

NFPA 1962- Firefighting Hose
 NFPA 1963- Fire Hose Couplings
 NFPA 1964- Firefighting Nozzle
 NFPA 1971-2018 Firefighting PPE

3rd PARTY TESTING INSTITUTES

UL-Underwriters Laboratories
 FM- Factory Mutual
 USA Certified Testing Laboratories



TITAN 800	DIA."	WORKING PRESSURE	BURSTING PRESSURE
WHITE	1-1/2"	300	750
	2-1/2"	300	750
TITAN-C 800	DIA."	WORKING PRESSURE	BURSTING PRESSURE
RED COATED	1-1/2"	300	750
	2-1/2"	300	750
TITAN 500	DIA."	WORKING PRESSURE	BURSTING PRESSURE
RACK HOSE WHITE	1.5"	250	500

BRASS FIRE HOSE NOZZLES

- 1 Monitor Nozzle- Adjustable Stream-NH Thread
- 2 Fire Hose Nozzle (Adjustable Stream) 2.5" BS336 x 12" Long
- 3 Fire Hose Nozzle (Straight Stream) 2.5" BS336 x 12" Long

MULTIPURPOSE BRANCHPIPE



- Firefighting Nozzle- 3-Way Spray
 Straight Stream, Fog and Combination
 Handle On/Off and Adjustment
 Aluminum Alloy Material Construction

Model CCM 1.5"- 9mm Nozzle Bore- 120 LPM
 Model CCM 2.5"- 12mm Nozzle Bore- 215 LPM

UL/FM HOSE RACK NOZZLES

Prevent Theft With Plastic Nozzles and Caps



BRASS ADJUSTABLE STREAM HOSE RACK NOZZLE
 1.5" NH Threaded Connection
 Straight Stream to Fog Spray Adjustment

PVC ADJUSTABLE STREAM HOSE RACK NOZZLE
 1.5" NH Threaded Connection
 Straight Stream to Fog Spray Adjustment



BS336 FIRE HOSE ADAPTER MALE PLUGS
 CHOOSE: Red Plastic or Black Rubber
 Complete With Chain

FIRE FIGHTING ACCESSORIES



3-WAY WYE VALVES

- Use with 2.5" Delivery Hose NH/BS336
- 2- 1.5" NH or 2.5" BS336 Outlet
- Aluminum Alloy or Brass Construction
- Ball Valve or Slide Shut-Off
- Optional Connections as Specied



FIRE TRUCK/ HYDRANT CONNECTIONS Threaded Reducers Brass-Chrome Plate



4" TH x 3" TH
4" TH x 3.5" TH



4" TH x 4" TH



Threaded Reducers
Brass-Chrome Plate
4" TH x 2.5" BS336



BI 336 (F) x 2.5" Thread



BI 336 (F) x 1.5" Thread

3-WAY WYE VALVE

USA

Select NH or BS336 Connection



RED HEAD
Mdl. 272NL



Brass/Plastic BS336 Plugs



Brass BS336 Caps

Truck Mounted Monitors



4" Flange or 3" Threaded Connection
Straight Stream Pipe or SS/Fog Adjustable Nozzle



Threaded Hydrant Connection
4" Inlet x 2-2.5" Outlet Cast Iron



Threaded Fire Department
Connection
4" Inlet x 2-2.5" Inlet
Polished Brass

WRENCHES

- ① Red Head P/N 101 (1" – 6" Pin or Lug)
- ② Red Head P/N 105 Hydrant/ Coupling
Hydrant 1.5" -1.7/8" & 1"-6" Coupling
- ③ P/N BEC W-580 Hydrant/Coupling
- ④ P/N FIR-04 Alum. Pin Lug Suction Hose
- ⑤ P/N FIR-04 Brass LH Lug Suction Hose
P/N FIT-T T-Style LH Valve Wrench




①




②



③



④



⑤

BEC W-580

FIR-04
FIR - 0304

FIR - T

HOSE COUPLING

HOSE COUPLING BS336 INSTANTANEOUS, STORZ AND NH (NST) THREADED

BS336- BRASS INSTANTANEOUS (FOR HOSE BINDING)

Working Pressure 300 PSI 5-Year
Warranty on Coupling & Binding




RED HEAD-USA NH COUPLINGS (EXPANSION RING)



Fire Hose Couplings 1.5", 1-3/4" and 2.5"
Brass and 1.5" -5" Aluminum Alloy
Rack Hose Couplings 1.5" Brass

BS336- ALUMINUM ALLOY INSTANTANEOUS



BS336 Types:

1.5" Hose x 2.5" BS336
1-3/4" Hose x 2.5" BS336
2.5" Hose x 2.5" BS336

TITAN BRAND NH HOSE ECONOMY COUPLINGS (EXPANSION RING)



Fire Hose Couplings 1.5"
Rack Hose Couplings 1.5"



BS336, BS (th), NH, Storz, ADAPTERS

STORZ ALUMINUM ALLOY COUPLINGS Storz Couplings for 1.5" and 2.5" Hose



Swedish and German Storz
1.5" - 4"

COUPLING SIZE CHART- BS336 INSTANTANEOUS, NH, STORZ, PIPE THREAD

INSTANTANEOUS BS336		STORZ (SWEDEN) (STORZ)		HOSE SIZE	COUPLING SIZE	NATIONAL STANDARD NH (NST)*		STRAIGHT IRON PIPE NPSH (IPT)		BRITISH STANDARD BSPT	
DIA	COUPLING	DIA	COUPLING	DIA	DIA	ODP	TPI	ODP	TPI	ODP	TPI
1.5"	1.5" / 2.5"	1.5"	1.5" / 2.5"	1.5"	1.5"	1.990	9	1.8788*	11 1/2	1.882	11
2.5"	2.5"	2.5"	2.5"	2.5"	2.5"	3.0686	7 1/2	2.841*	8	2.960	11
4"		2.5"	2.5"	4"	4"	5.0109	4	4.470	8	4.450	11

HOSE COUPLING INSTALLATION (HOSE BINDING AND EXPANSION RING)



BRASS ALUMINUM ALLOY

BS336 Instantaneous Couplings are
Installed: Inner Fabric Protection, #16
Stainless Steel Wire Binding and
Rubber Sleeve



E-Z BINDER HOSE BINDING MACHINE

Wire Bound Couplings Are Bound
With a Motorized High Tension Binding Machine.
Pressure Tested to 300 PSI



RED HEAD-USA BRUTE MODEL HOSE COUPLING INSTALLER

Installs Hydraulic Expansion Couplings 1.5" -5"
For more information: www.redheadbrass.com

FIREFIGHTING NOZZLE VIPER RYLSTATIC

**NEW
TECHNOLOGY**

NOZZLE “RYLSTATIC” FIREFIGHTING STREAM : “STRAIGHT”, “FOG”, “FOAM”




NFPA 1964 Compliant. EN-15182-1 And EN 151824 Type 3 Approved

TECHNOLOGY FIREFIGHTING STREAM : “STRAIGHT”, “FOG”, “FOAM” **Viper** Nozzles Flow Data


Model	Nozzle	Nozzle	Flow		Pattern	Reach Distance		Weight	Length
	PSI	BAR	GPM	LPM	Straight St.	Feet	Meters	Lbs.	Inch
BD-1560	580	40	55	210	Straight St.	112	34	3.8 (1.72)	8
BD-3012	580	40	123	465	Straight St.	141	43	4.2 (191)	9.25
BD-7515	100	7	150	560	Straight St.	148	45	4.2 (191)	9.25

BD-3012 (115-230-360-465-LPM) 1.5 NH INLET BD-1560 (50-100-160-210) - LPM
BD-7515 (280-360-470-560-LPM) 1.5 NH INLET BD-1560 1" BSP INLET


“RYLSTATIC” TECHNOLOGY IMPROVES PERFORMANCE



WATER VELOCITY
Less Friction Loss,
4.5% Increased Reach



STATIC PRESSURE
Reduced Static Pressure
Stable Flow From Straight to Fog



FOG PATTERN
Smaller Water Drops
Dense Fog/Water Mist

FIRE FIGHTING NOZZLE VIPER BRAND

ATTACK NOZZLE WITH ADJUSTABLE FLOW AND FIRE STREAM

Viper

VIPER FOAM ACCESSORIES

(For Use with Viper and Rylstatic Nozzles)

FOAM TUBE

BYPP FOAM EDUCATOR

(230LPM, 360LPM- X 3% & 6%)

FOAM TUBE

EDUCTOR



For Use With AFFF Foam 3% and 6%



Viper Nozzles Flow Data

Model	Nozzle	Pressure	Nozzle	Flow	Stream	Reach SS		Weight Lbs.	Length in.
	psi	bar	GPM	LPM		Feet	Meters	(Kgs)	
SG-3012	100	7	125	475	Straight	141	43	4.3(1.95)	8.85
SG-7515	100	7	150	600	Straight	148	45	4.3(1.95)	8.85

SG-3012 (115-230-360-475 LPM)

SG-7515 (265-380-500-600 LPM)

SPECIAL USE NOZZLES: SELECT FLOW, BRANCHPIPES, WATER CURTAINS

PROTEK HANDLINE

Instantaneous or NH Hose Connection



NFPA 1964 Compliant & FM

Model 366 (30/60/90/120 GPM)

Model 367 (95/125/150/200 GPM)


HIGH PRESSURE BRANCHPIPE



MODEL 9375- 1" BSPT Hose Connection

For Use With High Pressure Hose Reel to 40 Bar
Dual Pistol Grips for Safe Use at High Pressures
Straight Stream and Fog Flow Pattern

WATER CURTAIN




WATER CURTAIN HOSE CONNECTION

1.5" NH & 2.5" Instantaneous

Model 3265- 1.5" Waterway (800LPM) X=26m, Y= 7m

Model 9380- 2.5" Waterway (1200 LPM) X=32m, Y=10m

TECHNICAL CHARACTERISTICS



For More Information: www.tipsa.com

NOZZLE FLOW DATA

MODEL	PRESSURE BAR	FLOW	STREAM	REACH SS	WEIGHT (KGS)	LENGTH
PROTEK 366	7 BAR	120 GPM	SS	35m	1.7	228 mm
PROTEK 367	7 BAR	200 GPM	SS	35m	2.6	259 mm
POK 9375	40 BAR	200 LPM	SS	25m	2.8	520 mm

DELTA FIRE FOAM APPLICATION EQUIPMENT

DELTA FIRE



DELTA MOBILE FOAM UNIT MODEL DF 130

*IDEAL FOR PETROCHEMICAL & CHEMICAL STORAGE

130 L Wheel Foam Cart with Foam Inductor and Branch + Hoses (2)

Delta Inline Inductor Variable For AFFF, AFFF-AR and FFFP Foams 1%-6%

Optional Inline Inductor and Foam Branch 225lpm or 450LPM

BS336 Connection Standard or Optional Threaded, Storz or Q/C

Connections. Lloyds Registered and ISO 9002

DUAL EXPANSION FOAM BRANCHPIPE




IDEAL FOR CHEMICAL SPILL RESPONSE*

For Use with Delta Inline Foam Inductors

Dual Expansion Foam Branch Pipes Can Be Switched Between Low and Medium Foam Expansion by Moving a Lever. 3% OR 6% Foam.

Model L/MX 225 Application Rate: 225 LPM




OPTIONAL MEDIUM BRANCHPIPE

M225 - 225 Litres / Minute
M450 - 450 Litres / Minute

GRP- Long-life
Fiberglass Reinforced Plastic

DELTA FOAM INDUCTORS

For AFFF, AFFF-AR and FFFP Foams 1%-6%



Model Z 225-Application Rate: 225 LPM

Model Z 450- Application Rate: 450 LPM

Model Z 900- Application Rate: 900 LPM

HV (S) SERIES LOW EXPANSION FOAM BRANCH PIPES



For Use with AFFF, AFFF-AR & FFFP Foams
Standard HV Model Used with In-Line Inductors
Self-Inducting "S" Stand Alone (Built-in Foam Inductor)

2.5 in. BS 336 Inlet. DOT & Lloyds Standard

HV 225/ HV 225S 225 LPM @ 7 Bar

HV 450/ HV 450S 450 LPM @ 7 Bar

HV 900/HV 900S 900 LPM @ 7 Bar

HV Model HV "S" Self-Inducting

HIGH EXPANSION FOAM GENERATOR



IDEAL FOR WAREHOUSES, AIRPORTS UNDERGROUND SPACES & CONFINED SPACES

Combination Blower, Foam Inductor and Foam Net.

High Expansion Application to 200m/ min.

Expansion of Hi-Ex Foam to 1,200 x volume

Low Water Percentage Limits Water Damage

Model Delta "Excel" (Optional: Smoke Ejector Tubing)

*Must Use with Delta HI-EX High Expansion Foam (25L/pail) *

FAST ATTACK FOAM NOZZLE



IDEAL FOR CHEMICAL RESPONSE & FIREFIGHTING*

For Use with Delta Inline Foam Inductors

Slide Adjustable Head for Narrow or Broad Foam Application

Model DFA 225 Application Rate 225 LPM

Model DFA 450 Application Rate 450 LPM

TEMPEST PPV BLOWERS FOR FIREFIGHTING AND INDUSTRY

Tempest Positive Pressure Ventilation (PPV) Clears Smoke, Heat, Dust, Chemicals With A Powerful Force of Blown Air or Suction Smoke Together with the Ventilation Duct. AMCA Tested and Approved. Available as Engine or TEFC Electric/ Electric EP.

DIRECT DRIVE



"WINNING STEP"

**FLIP-UP
FOLD-DOWN**



**'AIR-FLEX' HIGH FLOW
COMPOSITE IMPELLER**



DIRECT DRIVE ENGINE DRIVEN MODELS (Choose Briggs and Stratton or Honda)

Model	Impeller Size Inches	HP	AMCA Tested CFM	Weight (Kgs.)
DD 18-B-5.5 (910-1121)	18	5.5	14,341	83
DD 21-B-5.5 (910-1141)	21	5.5	18,025	87
DD 24-B-5.5 (910-1161)	24	5.5	19,232	97


Model	Impeller Size Inches	HP	AMCA Tested CFM	Weight (Kgs.)
DD 18-H-4.8 (910-1120)	18	4.8	14,773	85
DD 21-H-5.5 (910-1140)	21	5.5	20,152	90
DD 24-H-5.5 (910-1160)	24	5.5	19,606	99

ANTI-STATIC, LAY FLAT BLOWER TUBING


(For Use in Smoke Ejection & Confined Spaces)

Standard Length 25 ft. (7.65 m) Extend Length by Joining

25 FT. (7.65M.)



8440-20	Use with 18 in. Blower
8440-22	Use with 20 in. Blower
8440-26	Use with 24 in. Blower



PPV VENTILATION IN LARGE WAREHOUSE

COLTRI BREATHING AIR COMPRESSORS

COLTRI SCBA AND SCUBA CYLINDER FILLING MACHINES

Fill Air Cylinders 200 & 300 Bar (2215-4500 PSI). 3 Stage Compressor Filling Rates 100-265 LPM.

10-20 minute/ Cylinder Filling Times Air Quality: DIN 3188 and EN12021. ISO 9001:2008 One (1) and

Two (2) SCBA or SCUBA Filling Lines Models Available with Gasoline Engines or 230V-380 V Motors

Options Include Hour Meters, Filling Cabinets (Water Filled)



MODEL MCH6/SH and

MCH6/EM-PORTABLE MODELS

TYPE: MCH6/SH (5.5 hp Engine) and MCH6/EM (230/1/50 2.2 Kw Motor)

Charging Rate: MCH6/SH-100LPM (6 m/h)

Charging Rate: MCH6/EM - 80LPM (4.8 m/h)



MCH 6/SH

MCH 13/16 SH



MODEL MCH13/DL and SH and

MCH13/EM-PORTABLE MODELS

TYPE: MCH13/DL (7 HP Lombardi Diesel) MCH13 (8 HP Honda)

MCH13/ET (230/1/50 5 Kw Motor)

Charging Rate: 215LPM (13 m/h)

Charging Pressure: 200/300 Bar (2216-4500 PSI)

Dimensions (Approximately) : 64x113x40 cms.

Weight: (140 Kgs.)



MCH 13/16 ET



HOUR METER

MODEL MCH16/ET (USE FOR FILLING CYLINDERS AND CASCADE SYSTEMS)

TYPE: MCH16/ET (380/3/50 7.5 HP 5.5 Kw Motor)

Charging Rate: MCH16/ET-265LPM (16 m/h)

Charging Pressure: 200/300 Bar (2216-4500 PSI)


Filling Time (Approx.): 6.8L (0-300 Bar) 8 min. 50L (0-300 Bar) 60 Min.

Dimensions (Approximately): 64x113x40 cm. Weight::160 Kgs.



TOTAL CARE, TRAINING, SALES, SERVICE FIRE, RESCUE, SAFETY

FIREFIGHTING NOZZLE REPAIR & TEST



- * Change Worn Parts
- * Clean and Lubricate
- * Test Flow and Volume
- * Test Nozzle Function



HOSE TESTING OF NEW and REPAIRED HOSE

Hose Tested to NFPA 1961 or BS 6391 Standards

Hose Testing of BS336 and Threaded Couplings

Test Certificate and Stencil on Hose Provided



COUPLING INSTALLATION & HOSE TEST

Install Wire Bound and Expansion Ring Couplings

Vulcanized Hose Repair of Rubber Hoses

Hydrostatic Testing of All Fire Hoses



RECHARGING OF DCP, CO2, LIQUID FILLED EXTINGUISHERS

- Recharge Extinguishers to Correct Weight, Pressure, Rating
- Firefighting Chemical
- Repair and Replace Worn and Defective Parts
- Hydrostatic Testing of CO2 and DCP Cylinders

SCBA INSPECTION, CYLINDER TESTING AND REFILLING

- * Inspection and Repair of Most Brands of SCBAs'
- * Repair and Replace Worn and Defective Parts
- * Hydrotest of Compressed Air SCBA Cylinder
- * SCBA Proper Use and Inspection Training

AMKUS HYDRAULIC RESCUE TOOL TRAINING and REPAIR



- Vehicle Rescue Extraction Training and Safe Operation
- Set-up and Patient Safety
- Maintenance and Proper Use of Amkus and Paratech Rescue Equipment

FOAM TESTING AT UK CERTIFIED LAB TO BE AND EN STANDARDS



FIREFIGHTING SUIT REPAIR

- Repair and Replace Worn and Damaged Shell Material
- Replace Worn and Damaged Trim (Reactive, Leather, Fabric)
- Replace Thermal and Moisture Lining on all BSP Brand Suits
- Helmet Repair and Replacement of Defective and Damaged Parts

SERVICE EQUIPMENT



E-Z BINDER- HOSE BINDER

Motorized Wire Hose Coupling Binder. Tightly Wire Bind BS 336 And All Couplings with Hose Ends 1-4 inches.



RICE HOSE TESTERS-1-4 OUTLETS

Test Hoses to 500 psi (34 Bar) Fire Hoses Hydrostatically Tested To NFPA 1961 and BS Standards Mdl. EL-FHT (2 Outlet) and FHT (4-Outlet)



STENOR HOSE REPAIR SYSTEM

Repair Holes and Cuts in Extruded Rubber Firefighting Hose 1-6 inches Red and Yellow Repair Patches 200 PSI (13.7 Bar) Working Pressure.

SCBA & SCUBA CYLINDER FILLING MACHINE

SCBA



SCBA AND SCUBA CYLINDER FILLING MACHINE

Fill Air Cylinders 200 & 300 Bar (2215-4500 PSI) Filling Rates 100-265 LPM. 10-20 minute/ Cylinder Filling Times One (1) and Two (2) SCBA or SCUBA Filling Lines Models Available with Gasoline Engines or 230V-380 V Motors Options Include Hour Meters, Filling Cabinets (Water Filled)



VANZETTI

FILLING MACHINES

TOTEM-T 12-15 Kg/MIN

TOTEM MINI - E 8-10 Kg/MIN

E-Z CLAMP STATION

WATER FLOW KIT

- U.L. classified for testing
- Six machined tips measure flows ranging from 110-1600 gpm (400-6000 lpm) at 40-120 psi (280-830 kPa)
- Holds pitot tip firmly in correct stream position - eliminates many variables caused by hand-held units
- 1% full range accuracy
- Complete with tough, molded carrying case, instruction booklet and laminated flow chart
- U.S. standard measurements or metric equivalents
- Standard tip Sizes: 3/4", 1 1/8", 1 1/2", 1 3/4", 2", 2 1/4"
- Style FK-25



PITOT GAUGE



Measures straight tip pressure to determine flow or pumping capacity. Blade is calibrated for various tip sizes.

- Style HH-Pitot
- Petcock for bleeding off air
- Includes Style 91000 Fire Stream/Friction Loss Calculator and protective carrying case
- Weight: 4 lbs.

STYLE HH - PITOT
With Style 91000 Fire Stream/Friction Loss Calculator



PUMP & ACCESSORIES



BAND - IT



DELIVERY HOSE LAY-FLAT OR HARD SUCTION

- ① ARMTEX 4"-6" Lay Flat Delivery Hose and Red Head Delivery Hose Couplings 4-6" NH (Red Head Storz Couplings Available)

COUPLINGS AND ADAPTERS


- ② Red Head Style 7700 Rocker Lug or LH (Female) (2)
Red Head Style SKT Kwik -Tach Storz Couplings 4 in. -12 in.(2)
- ③ Red Head Double Female Adapter (Rocker Lug or LH)
-Style 299- LH Female Suction Hose Coupling
-Style 53RL- Rocker Lug Swivel F x Rigid Female (4)
-Style 35- Double Swivel Female Rocker Lug (5)
-Style 57- Double Long Handle Female (Swivel x Swivel) (5)
-Style 37- Rigid Rocker Lug Female to Male

Assembled with Band-It Bands and Clampsor Screw Clamps


- ⑦ Hard Suction Hose in White or Black. 3 in, 3.5 in and 4in.
Diameters Lengths available 3m and 9m.
Various Suction Coupling Threads Available.
- ⑧ - ⑨ Suction Strainer in 3 in., 3.5 in. and 4 in.
Available in Aluminum and Brass (9)
- ⑩ Suction Strainer with Foot Valve.
- ⑪ Basket Strainer for Covering Metal Strainer

DIESEL DRIVEN FIRE PUMP- Model YDP20MHE

- Standard for Use in Boat and Vessels
- Yanmar 4.7 H.P. Diesel Engine. 3,600 R.P.M.
- 12 v. Electric Start and Recoil Pull Start
- Impeller Pump with Electric Suction
- Capacity: 500 LPM at 7 M.
- 2" (50MM) SUCTION HOSE (9 M) + FOOT VALVE & STRAINER
- NON-CORROSIVE FEATURES AND FRAME + COVER
- Weight: 40 KGS. Foam Nozzle (Optional)
- Durable and Comfortable Water Sack and Carry Straps



RESCUE EQUIPMENT



SPINE BOARDS "USA Made"

① **JSA-365** Spine Board. 12 Hand Holes for Easy Lifting. **JSA-365S** (Speed Clips) One-piece Construction. Built-in Runners on Bottom Protects Spine Board and Patient.

X-ray Without Removing Patient from Spine Board. Capacity 400 lbs. (182 Kgs.) Length: 72 in. (183 cm). Width 16 in. (41 cm.) Thick: 1.75 in. (4.5 cm) Suitable for Conned Space and Vehicle Rescue.

Accessories:

- ② **JSA-363-BF** Head and Neck Immobilizer. Head Support Attaches to Spine Board by Velcro Straps. Adjustable with Ear Holes. Removable Pads for Smaller Heads.
- ③ **JSA-360-S** Adjustable Locking Straps with Q/R "Seat Belt" Locking Mechanism



FIRE BLANKETS

(Fire and Wool Wrap - around Extinguishing)

JUNKIN JSA1002

Wool Fire Blanket
100% Wool. Extinguishes Fire by Wrapping Around Person, Water Immersion Not Required.
Size: 62" x 82"



① WATER-JEL COATED FIRE BLANKET

Water-jel-Medicated Jel Coated Fire Blanket
Extinguishes Fire and Protects Burns on Persons.
Size: 6 ft. x 5 ft. (183 x 152 cm)




MADE IN U.S.A.



JUNKIN STRETCHERS- "USA Made"

- ① **JSA -601-NA** "EASY-FOLD" ALUMINUM POLE STRETCHER
Length: 86". Light Weight: 14 lbs. (6.4 Kgs.) Capacity: 300 lbs. (137 Kgs)
Wooden Handles, Aluminum Frame, HD Green Vinyl Coated Nylon Base (Clean & Disinfect)
- ② **JSA-602** "EASY FOLD" "WHEELED" STRETCHER
Length: 74". Light Weight: 13 lbs. (6.0 Kgs.) Capacity: 300 lbs. (137 Kgs)
Wheels, Aluminum Frame, HD Green Vinyl Coated Nylon Base (Clean & Disinfect)
- ③ **JSA-603** "EASY FOLD" LAY FLAT STRETCHER
Length: 74". Light Weight: 13 lbs. (6.0 kgs.) Capacity: 300 lbs. (137 Kgs)
Wheels, Aluminum Frame, HD Green Vinyl Coated Nylon Base (Clean & Disinfect)
(Lay-at style. Same as JSA-602, without wheels)
- ④ **JSA-400** ALUMINUM BREAK-APART STRETCHER
Stretcher separates side-to-side & length to length. Use where patient cannot be lifted or rolled without further injury. Stretcher can be separated in middle for x-ray. Includes three (3) restraint straps.
Length Adjustable: 49.5" to 80". Light Weight: 21.5 lbs. (9.8 Kgs.) Capacity: 400 lbs. (181 Kgs). Aluminum, Frame Lay-at style. Can be cleaned & disinfected
- ⑤ **JSA-300 + JSA-302 + JSA-300X** BASKET STRETCHER C/W COMFO-PAD & SLING
Light-weight basket stretcher. Three (3) restraint straps. JSA-302 Comfo-pad orange HD vinyl provides cushion for patient. Can be cleaned and disinfected. JSA 300X Bridle Sling allows stretcher to be lifted horizontally or vertically. Capacity 2,000 lbs. (909 Kgs.) Length: 80.5". Width: 22.5" Weight Stretcher: 31 lbs. (14.0 Kgs.) Capacity: 300 lbs. (137 Kgs)
Includes: Basket Stretcher, Pad, Sling. (Can be used with Eze-Man Tripod)
- ⑥ **JSA 300CS+ 302 +300X** "CS" BASKET STRETCHER C/W COMFO-PAD & SLING
19 in. wide (7.5cm) for use in Conned Space Rescue. Same construction details as JSA-300
Length: 81.5". Width: 19" Weight Stretcher: 23 lbs.(10.5 kgs.) Capacity: 300 lbs. (137 kgs)
Includes: "CS" Stretcher, Pad, Sling. (Can be used with Eze-Man Tripod)
Note: All Junkin Safety Stretches are manufactured in the USA and certied under Mil-Spec and 3rd Party Test reports.



② TOP-SPEC COATED EXTINGUISHING BLANKET

Synthetic -Glass Reinforced and Coated
Fire Retardant Fire Blanket Puts Out Fires
Without Chemicals or Water. Storage Case Included
Sizes: 1.2 x 1.2m, 1.2 x 1.8m and 1.8m x 1.8M



THAILAND MADE FOLDING STRETCHERS

- ① **Model TH001** Aluminum Frame/ Vinyl Base Straps and Carry Bag Included.
- ② **Model TH002** Economy Stretcher
Aluminum Frame / Vinyl Base Folds Lengthwise

EMERGENCY ESCAPE RESCUE EQUIPMENT

ESCAPE-RITE AUTOMATIC DESCENT SET



ESCAPE-RITE MODEL 1003

- Allows for Emergency Escape with Minimum Training
- Automatic Descent at Rate 1 Meter/ 1 Sec.
- Strong, Heat and Fire Resistant Poly Steel Coated Cable
- Maximum Length (300 ft.) (100 meters) or 30 Story Building (Approx.)
- Double Adjustable Belts Allow for Rapid Alternating Descent
- Made in the USA with Safety Test Certificate and Operation Manual



Directions for use:

1. Attach Escape-Rite to Fixed Point
2. Place belt below arms & around chest
3. Grip tightly and ascend to ground
4. As the person lowers, the second belt ascends.
5. No special training, Automatic controlled descent



Locations for Emergency Escape:

1. High rise buildings
2. Hospitals, Hotels, Department Stores
3. Power Plants, Refineries, Construction Sites
4. Use together with Full Body Harness & Basket Stretcher



THE LIFE CUBE™ RESCUE JUMPING CUSHION

- For Use in Catching Persons jumping or falling from up to 10 stories
- Light-weight and Durable Flame Resistant Fabric Construction
- Inatable tube structure that inflates with use of Air Cylinder (no need for fans, generators or electrical connections to operate)
- Light-weight, Quick set-up, Moveable without deating, Safe
- DIN 14151 Standard. English Instructions, On-site Training.



1

1. Move to jump site and unpack. (0 seconds)



3

3. Life Cube™ Takes Shape (25 seconds)
Fully Inflated (30-35 seconds)



5

5. First Jump (40 seconds)



4

4. Ready for First Jump (30 seconds)



6

6. First Jump Completed (45 seconds)
Ready for Second Jump



2

2. Open Valve 8L, 300 Bar air cylinder to inflate (3 seconds)

TOOLS FOR RESCUE & FIRE FIGHTING



MODEL FIR-2000 MULTI-FUNCTION TOOL SET

Tools Set Includes: Screwdriver Set (Straight & Phillips) Drilling Hammer, Hacksaw and Blades, Folding Shovel Cutting Plier, Adjustable Wrench, Cable Cutter, Duct Tape Plug Seal Kit, Seat Belt Cutter, Pry Bar, Optional: Biel Tool



PARATECH MDL 715 HAZMAT PLUG KIT

Plug Leaks 3/4" – 4". Wood Plugs x 3.
Rubber Plugs x 3.
Non-Sparking Hammer + Box



PARATECH 700 SEAT BELT CUTTER

Slices Woven Seat Belts for Vehicle Rescue Metal Tip "DZUS" for Breaking Non-laminated Glass Easy-Grip Handle. Length: 24cm. Weight: 5 Kgs



SOS RESCUE TOOL SET

16 Function Rescue Tool Set. Cutting, Prying, Piercing, Digging Functions with Interchangeable Head and Handles. 12 Pieces per Set.

① P/N 80001- Set Contents in Vinyl Holster

② P/N 80002- Set Contained in Plastic Case



TEMPEST MODEL 375K VENTMASTER CUT-OFF SAW

Cuts Metal, Block, Concrete. Cutting Capacity to 14 in. Cutting Depth 4.75 in. 5Hp (74.7cc) 2-Stroke Engine Metal, Concrete and Carbide Rescue Saw Blades Incl.

Optional: Metal Carry Case, Gas Can and Tool Kit



CHAIN & CABLE CUTTERS- 24" USA MADE

P/N 0190FC Electric Cable Cutter- Fiber Handle

P/N 0190MC Electric Cable Cutter- Metal Handle



FIRE AXE- Thai Made* and Import

P/N FIR-03 14 in. Personal Axe

w/ Sheath*

P/N FIR-06 14 in. 6 lbs Axe x 36" Long*

P/N 406x Fire Axe (Wood or Fiber Handle)



PRY BARS- Pry, Pull, Lift

P/N 41004 36 in.

Gooseneck- USA

P/N FIR-120 1.2m

Straight Pry Bar



FIRE LADDERS (Aluminum and Fiber)

P/N AE 4000 Extension Ladder
Fiberglass 20-40 Ft. (6-12M)

FIR-101520 Thai Made Single
Ladders to 12' (3.6 M)

FIR-15 Thai Made Extension
Ladders- to 15' (4.5M)



FIRE STRIKING (SLEDGE) HAMMERS

P/N 62-327 Drilling Hammer
6 lbs./ 16" Long

P/N 1438G Sledge Hammer
10 lbs./36" Long

P/N FIR-08 Thai Made Sledge
8 lbs./36" Long

PARATECH RESCUE TOOLS



PARATECH



PAKHAMMER AIR OPERATED RESCUE IMPACT HAMMER
Model PAKHAMMER KIT 10 Piece Penetration Set for Rapid Rescue



MAXIFORCE G2 HIGH PRESSURE AIR LIFTING BAGS **MAXIFORCE LOW PRESSURE, HIGH LIFT AIR CUSHIONS** **MULTIFORCE AIR LIFTING BAGS**

Maximum Lifting Capacity: 130,000 Kgs. @ 8 bar Pressure
Maximum Lifting Height: 1M. For Use in Rescue and Vehicle Extraction
BASIC SET: Two Lifting Bags, Regulator and Control Package, Air Cylinder.
Larger Sets Use Multiple Bags, Hoses and Larger Control Package



Model AIRGUN KIT 9 Pc. Penetration Set for Confined Space

Model AIRGUN SC KIT Self-Contained Kit for Rescue and Specialized Fire Fighting.
Pakhammer Kit Provides Basic Set for Penetration of Block, Metal and Concrete. The Kit Can Be Expanded by Adding Additional Tool Bits. 400 Blows Per Minute (BPM)
Airgun Kit and Airgun SC Kit Provide Basic Set for Penetration of Block, Metal and Non-Reinforced Concrete. The Kit Can Be Expanded by Adding Additional Tool Bits. 600 (BPM)



HOOLIGAN PRY AND PENETRATE TOOLS

Pry, Pound, Puncture, Twist and Cut to Remove Barriers to Entry. 3 in 1 Construction
Includes, Claw (Standard or Metal Cutting), Piercing Point and Pry Head
Mdl. 600* 30 in. Long. Standard Claw
Mdl. 430* Lightweight
Mdl. 601* 36 in. Long. Standard Claw
Mdl. 623* Highway Rescue Metal Cutting



PRT FORCIBLE ENTRY and PENETRATION TOOL SET

8 Pc. Set Allow the Team to Slam and Ram Through Metal, Concrete Block and Brick in Quick Time. Break Locks, Pry, Lift, Separate in Rescue, Tactical and Fire Fighting.

PERSONAL FORCIBLE ENTRY TOOLS

Model Biel - Personal Entry Hand Tool for Vehicle and Building Rescue

Model Titan Crash Tool - Multi-Use HD Rescue Hand Tool

Model Pry - Axe Multi-Purpose "Slam and Ram" Rescue Hand Tool

Paratech Rescue Struts Load Table			
Working Load Chart at Following Safety Factors		4:1	
Length (ft)	Weight (lbs)	25,000 (1:154.5)	21,750 (988.6)
21.6	43,500 (19721.3)	29,000 (13154.2)	21,750 (988.6)
43.2	86,900 (39442.6)	58,000 (26308.4)	43,500 (19721.3)
64.8	130,300 (59163.9)	87,000 (39462.6)	65,250 (29581.9)
86.4	173,700 (78745.2)	116,000 (52616.8)	87,000 (39462.6)
108.0	217,100 (98326.5)	145,000 (65771.0)	108,750 (49353.2)
129.6	260,500 (118447.8)	174,000 (78825.2)	130,500 (59578.5)
151.2	303,900 (138069.1)	203,000 (92379.4)	152,250 (69130.7)

Working loads shown at 4:1 ratio.

5 Year Warranty

The data in this table has been confirmed by physical testing, witnessed and certified by an independent, licensed structural engineering company.



PARATECH RESCUE STRUTS

Strut Kits Stabilize Buildings, Trenches and Vehicles
Where the Safety of the Injured and the Rescue Operator and Operator is Most Important. Air Operated Sets Include the Strut, Base, Tip and Control Equipment.
Manual Sets Can be Quickly Set-up and Placed As Required. Many Specialized Sets Available for Vehicle for Every Requirement




PARATECH, PRY, PULL, CUT - FORCIBLE ENTRY TOOLS



BIEL TOOL - One Piece Stainless Steel Personal Entry Tool. Five (5) Function Rescue Tool Small Enough to Be Carried by the Firefighter or EMT Member. Force Open Doors and Windows. Twist and Break Locks and Metal Bars. Cut Sheet Metal and Break Car Windows for Vehicle Entry. Size: 38 cm long x 1.5 Kgs.

PRY-AXE - Two Piece Multi-Purpose Ten (10) Function "Slam and Ram" Personal Entry Tool for Use by Police and Fire Departments. Pry Open Doors and Metal Compartments. Twist Off Locks and Latches. Cut Through Sheet Metal and Pry Off Window Bars. Entry Into Vehicles by Breaking Glass or Cutting Sheet Metal. Easy Mounting in Vehicles or Motorcycles. Size 47 cm long x 3 Kgs.




HOOLIGAN TOOL - Pry, Puncture, Pound, Twist and Cut In the Most Demanding Entry Applications. Six (6) Function Tool for Fire and Rescue. Choose Metal Cutting or Standard Claw. Select From Lengths: 24 in (61 cm) to 42" (106 cm). Three (3) Basic Models: Hooligan Standard Tool, Hooligan Lightweight (Aluminum Handle) and Hooligan Spark Resistant Tool For Use in HazMat Incidents.




PRT RESCUE KIT - Hand Operated Percussion Rescue Tool (PRT) The Sliding Ram Directs the Force of Impact At The Tool for Breaking, Puncturing, Cutting and Prying When Fast Entry is required. Five (5) Tools and One (1) PRT Ram Bar In A Carry Pouch. Accessories Available included Piercing Applicators for Firefighting Applications. Weight: 13 Kgs.

for additional information visit: www.paratech.com

PARATECH-LIFT AND SHIFT



MAXIFORCE AIR LIFTING BAGS- Air Operated (10.3 Bar) with Lifting Capacity to 80 MT to a Maximum Height of 55 cm. Insertion Height on 3cm. Set consists of 1-14 Air Lifting Bags Control Set (Regulator, Controller, Hoses and an Air Cylinder or Other Air Source). Suitable for Rescue, Vehicle Extraction and Industrial Applications. Complete Specifications available. Training included Upon Request.




MULTIFORCE AIR LIFTING BAG- Dual Lifting Bag Provides Safe, High Load 28MT Combined with High Lift to 66cm. Insertion Height only 11.4cm. Choose from Three (3) Kits to Meet Your Application, "Remote Placement Multiforce", "Basic Multiforce" and "Compact Multiforce". Complete Specifications available. Training included Upon Request.

MAXIFORCE 22-890351G2 34 TON-2 BAG SET WITH BASIC CONTROL KIT

MAXIFORCE 22-889050G2 50 TON-3 BAG SET WITH BASIC CONTROL KIT

MAXIFORCE 22-888190G2 VEHICLE SET WITH BASIC CONTROL KIT



CONTROL KITS AND MAXIFORCE AIR BAG SETS

BASIC CONTROL KIT 22-890351G2D- Includes Regulator, Dual Deadman Control and Hoses

MASTER CONTROL KIT 22-890351G2D- Includes Regulator, Dual Deadman Control, Hoses and Selection of Fittings and Connections for Use With Multiple Air Bag Applications.



for additional information visit: www.paratech.com

AIR POWERED IMPACT TOOLS



The **AIRGUN KIT** is a Portable Twelve (12) Piece Air Powered Light Weight, Light Duty Tool for forcible entry and rescue work. Use Together with SCBA or Spare Air Cylinder. The **AIRGUN KIT** includes Three (3) Specially Designed Tool Bits for Cutting, Breaking and Penetrating. Cut Sheet Metal, and Locks. Create Entry Through Masonry Walls. Very Low Air Consumption and High Impact Output, at 1600 Blows Per Minute. Weight only 7 pounds (3.2 kg), the **AIRGUN KIT** is an ideal tool for rescue work. Additional Bits May Be Purchased for Haz-Mat, Firefighting and Vehicle Rescue.



The **AIRGUN SC KIT** is a Portable Twenty-Four (24) Piece Air Powered Light Weight, Light Duty Tool for Firefighting, Forcible Entry and Rescue Work. Use Together with Mounted Air Cylinder, SCBA or Spare Air Cylinder. **AIRGUN SC** Contains Ten (10) Specialized Tool Bits Including Two (2) Piercing Applicators. A Firefighter Can Rapidly Deliver Water, AFFF Solutions and Halon Through the Skin of An Aircraft or Water Tight Compartment. Additional Specialized Tool Bits Are Used for Cutting Sheet Metal, Vehicle Extrication, Lock Breaking, Entry Through Masonry Walls. The Self-contained Air Supply Can Be Removed, and An External Air Cylinder Connected for Prolonged Use. 1600 Blows per Minute. Weight 8.9 Kgs. Completely Assembled.



The **PAKHAMMER KIT** is a Portable Twelve (12) Piece Air Powered Light Weight, Medium Duty Tool for forcible entry and rescue work. Use Together with SCBA or Spare Air Cylinder.

The **PAKHAMMER KIT** includes Three (3) Specially Designed Tool Bits for Cutting, Breaking and Penetrating. Cut Sheet Metal, and Locks. Create Entry Through Masonry Walls. Very Low Air Consumption and High Impact Output, at 1100 Blows Per Minute. Weight only 11 pounds (5 Kgs), the **PAKHAMMER KIT** is an ideal tool for rescue work. Additional Bits May Be Purchased for Haz-Mat, Firefighting and Vehicle Rescue.

AMKUS ENGINE DRIVEN HYDRAULIC RESCUE TOOLS



MODEL GOLDEN HOUR



MODEL "GOLDEN HOUR" HEAVY DUTY SET CONTAINS:

- Model GB2S-XLO Hydraulic "Simo" Power Unit NFPA/EN with Standard Twin Hoses or Amkus "Mono-Coupler" Hose
- Model AMK-24 NFPA/EN Certified Spreader
- Model AMK-21A NFPA/EN Certified Cutter. Rotating Handle
- AMK-40 Push-Pull Ram. 10" Ram Extension (Optional)
- Quick Adjust Chain Package



MODEL ALPHA II

MODEL "ALPHA II" QUICK RESPONSE SET CONTAINS:

- Model GH2- MC Mini Hydraulic "Simo" Power Unit with Roll Cage
- Standard Twin Hoses or Amkus "Mono-Coupler" Hose
- Model AMK-25C Combination Cutter/Spreader W/ D-Handle
- AMK-30 Push-Pull Ram and 10" Extension
- Manual Adjust Chain Package



MODEL CLASSIC III

MODEL "CLASSIC III" HEAVY -DUTY RESCUE SET CONTAINS:

- Model GB2S-XLO Hydraulic "Simo" Power Unit NFPA/EN
- Standard Twin Hoses or Amkus "Mono-Coupler" Hose
- Model AMK-30CX Light Weight, Full Size Spreader
- Model AMK-25 Heavy Duty, High Performance Cutter
- AMK-40 Push-Pull Ram. 10" Ram Extension (Optional)
- Quick Adjust Chain Package



AMKUS BATTERY POWER HYDRAULIC RESCUE TOOLS



ION iC550 CUTTER

- Cutter blades and center bolt are designed to access tight places and make difficult cuts
- High intensity integrated LED lights illuminate the work area
- Rotating handle allows tool to be repositioned with minimal effort

Length	29.2 inches (741 mm)
Width	6.9 inches (175 mm)
Height	8.6 inches (218 mm)
Weight (excl. battery)	44.4 lbs (20.1 kg)
Cutter Opening	5.9 inches (150 mm)
Cutter Rating	A6/B6/C7/E7
Battery	Dewal® Lithium-Ion
Battery Voltage	36V

ION iS240 Spreader

- The iS240 uses the same tips as the hydraulic AMK-24 and AMK-30CRT, including the ERT tips and the quick adjust chain package
- Adding ERT tips to the iS240 expands the spreading distance.

Length	30.1 inches (764 mm)
Width	7 inches (177 mm)
Height	8.8 inches (223 mm)
Weight (excl. battery)	46.2 lbs (21 kg)
MAX Spreading Distance	24 inches (609 mm)
MAX Spreading Distance (with optimal ERT tips)	32 inches (813 mm)
Battery	Dewal® Lithium-Ion
Battery Voltage	36V



ION iCT516 COMBI TOOL

- Versatile and durable “first on scene” tool for rescue truck or ambulance
- The iCT516 Combi Tool can be used to spread, cut and “pop” doors

Length	28.9 inches (734 mm)
Width	6.9 inches (175 mm)
Height	8.6 inches (218 mm)
Weight (excl. battery)	44.9 lbs (20.3 kg)
MAX Spreading Distance	15.6 inches (396 mm)
Cutter Opening	7.3 inches (185 mm)
Battery	Dewal® Lithium-Ion
Battery Voltage	36V



ION iTR230 RAM

- The iTR230 has the highest pushing force available in a battery power ram
- Unique rotating handle allows extra maneuverability in tight spaces
- Extensions available for a maximum extended length of 50 inches

Length	17.0 inches (432 mm)
Width	7.9 inches (200 mm)
Height	11.4 inches (290 mm)
Weight (excl. battery)	4.4 lbs (20.1 kg)
Length Retracted	11.4 inches (290 mm)
Length Extended	22.6 inches (574 mm)
Stroke : Piston 1	6.3 inches (160 mm)
Stroke : Piston 2	4.9 inches (124 mm)
Stroke : Overall	11.2 inches (284 mm)
Extensions Lengths Available	10, 18 and 27 inches (254, 457 and 686 mm)
MAX Extended Length with Extensions	49.6 inches (1260 mm)
MAX Pushing Force Piston 1	48,061 lbs (213.8 kN)
MAX Pushing Force Piston 2	17,417 lbs (77.4 kN)
Battery	Dewal® Lithium-Ion
Battery Voltage	36V

SAFETY LIGHTING

WORKSAFE ALKALINE - The WorkSAFE series includes 2D and 3D-sized flashlights (both available in waterproof models), lanterns, All UL Class I, Division I rated for unsurpassed safety in the most hazardous environments and they're all affordable enough to meet even the most modest budgets. Waterproof and floats. Polyethylene body. UL standard embossed on body.

Division 1 WorkSAFE™ I

HAZARDOUS AREA

MODEL NUMBER	Type Designation	MSHA Approved	Underwriter Laboratories Division 1			
			Class I Group C	Class I Group D	Class II Group G	Class III
13740 / 14460	II	✓	✓	✓	✓	✓
14240 / 14720	II	✓	✓	✓	✓	✓
2206	II	✓	✓	✓	✓	✓



- 1.(2-D Cell) Model 13740 (2117) (Value Model) Model 14460 (2217) (Best Model)
 - 2.(3-D Cell) Model 14240 (2114) (Value Model) Model 14720 (2224) (Best Model)
 - 3.(6-V Cell) Model 07050 (2206) Lantern Style with Glove Size Handle
- ** Value Model (brass switch contact) Best Model (steel and brass switch contact)
- * Batteries not included

DATA SHEETS: <http://www.flashlight.com/worksafe-alkaline/>

PELICAN SAFETY FLASHLIGHTS Xenon Bulbs * Hazardous Location * Water Resistant

FM PELICAN



** Must use "Alkaline" Batteries for maximum bulb life

- 1.Model 2400C-Stealthlite 45 Lumens One hand switch + Model 700 Helmet Mount (4AA cell-included)
- 2.Model 2000C-Saberlight 53 Lumens Lens Shroud Twist on/off
- 3.Model 1900C-Mitylight Lens Shroud Twist on/off


CERTIFICATIONS: Class I, Division 1 / Class I, Division 1 / Class II, Division 2 / IECEx ib

DATA SHEETS: <http://www.pelican.com/us/en/pro/products/safety-ashlights-and-headlamps/>

RECHARGEABLE

Qualication of Rechargeable

1. Charge 12V / 220V
2. Complete Set include 6V battery and charger
3. Adjustable handle for carry



MAG INSTRUMENT

- 1.P/N M2A01H Flashlight With Pouch (2-AA cell)
2. P/N S2D016, S3D016, S4D016 (2-D cell , (3-D cell) , (4-D cell)
3. P/N S6D016 (6-D cell)

www.maglite.com

MAG INSTRUMENT Incandescent Bulb *Water Resistant* Aluminum Body

Every Mag-Lite ashlight embodies a precise balance of rened optics, efcient power, durability and quality. Each Mag-Lite D-Cell flashlight includes two high intensity White Star Lamps for enhanced brilliance and extended range.

- 1.Model M2A01H-Mini maglite Compact flashlight + cloth holder
- 2.Model S2D016 (2-D Cell) S3D016 (3-D Cell), S4D016 (4-D Cell) Full Size Flashlight
- 3.Model S6D016 (6-D Cell) 178 Lumens

LED SAFETY LIGHTING



BRIGHTSTAR WORKSAFE LED

- For use in hazardous situations
- Division 1 Class 1
- World's Most Affordable
- Waterproof
- Anti-roll tube



WorkSafe™ Model # 2217- #15460 LED (2-D CELL)

Power Source: 2x 'D' Cell Alkaline Light Source: LED
Life: 30,000 hrs Runtime: 200 hrs Light Output: 80
Lumens Beam Distance: 99 Meters

WorkSafe™ Model # 2224- # 15720 LED (3-D CELL)

Power Source: 3 x 'D' Cell Alkaline Light Source: LED
Life: 30,000 hrs Runtime: 250 hrs Beam Distance: 88
meters Light Output: 60 Lumens



PELICAN LED LIGHTS

The new **3315 LED** ashlight: the lightweight compact design houses 3AA batteries that power a single LED for 160 lumens of super bright LED light.

CERTIFICATIONS: Class I, Division 1 / Class II,



#700 HELMET LITE HOLDER FOR SAFETY AND FIREFIGHTING



The **2690** is made of impact and chemical resistant ABS and it's water resistant for all-weather use. It comes with an adjustable and comfortable cloth strap, as well as a heavy duty rubber strap that will not slip off your climbing helmet or hard hat. 74 lumens of LED light, 11 hours of battery run time and weighing in at 4.1 ounces CERTIFICATIONS: Class I, Division 1 / Class II, Division 1 / Class III, Division 1 / IECEx ia



MINI MAGLITE® LED FLASHLIGHT

145 m Beam
97 Lumens

MAGLITE® 2-CELL D LED FLASHLIGHT

412 m Beam
168 Lumens

MAGLITE® 3-CELL D LED FLASHLIGHT


412 m Beam
168 Lumens

JUSTRITE CHEMICAL STORAGE

CHEMICAL STORAGE CABINETS FOR FLAMMABLE, ACIDS, AND CORROSIVES



STORAGE CABINETS FOR FLAMMABLE, COMBUSTIBLE & CORROSIVE MATERIALS



Add a ramp for convenience!
Sturdy clips securely join ramp to pallet edge for a snug fit.




SAFETY STORE ALL CHEMICALS IN JUSTRITE SAFETY CANS, CONTAINERS, CABINETS AND SPILL CONTROL PALLETS. ALL JUSTRITE PRODUCTS ARE COLOR CODED TO IDENTIFY THE TYPE OF CHEMICALS STORED. ALL CABINETS AND STORAGE PRODUCTS MEET INTERNATIONAL STANDARDS SUCH AS OSHA AND NFPA CODE 30 TO ASSIST YOUR COMPANY IN MEETING ISO 1800 AND ISO 14000 REQUIREMENTS.



Gator® Accumulation Centers

Product Description	Sump Cap. (Gallons)	Load Bearing Capacity	Outside Di W x D x H m.	Model No.
2 drum unit	22	2400 lbs.	49" x 25" x 51/2"	28922
4 drum unit	43	6000 lbs.	49" x 49" x 51/2"	28923
6 drum unit	64	7000 lbs.	73" x 49" x 51/2"	28923
8 drum unit	85	8000 lbs.	97" x 49" x 51/2"	28924
Ramp for above	-	1000 lbs.	48" x 33" x 51/2"	AK28905
Joining clips, one pair, stainless steel	-	-	4" x 2"	AK28906
Sump-to-Sump™ Drain Kit	-	-	-	28926
	-	-	-	28927

COLOR CODE FOR HAZARDOUS MATERIALS



www.justritemfg.com

CAPACITY 1-5 USG (4-19 L)



PARATECH LEAK PLUG KIT
Plugs Leaks and Holes " -4"
Neoprene Plugs (3)
Wooden Plugs (3)
Includes Non-Sparking Hammer and Storage Case. **P/N 715**



OIL SPILL CONTROL MATERIALS
- Oil Spill Booms
- Oil Spill Pillows, Pads
- Oil Spill Containment Tape and Epoxy Putty
- Gloves and Chemical PPE



OIL SPILL CONTAINMENT KIT
Self-Contained Portable Chemical Spill Kit
- Contain Spills up to 14 Gallons (53 L)
- Included Booms, Pillows, Pads for Absorbing Oil and Chemical Spills. Basic PPE for the Worker



This Kit even fits through narrow aisles and doorways!

LINE CARD

Devcon

Devcon

Metal Repair and Wear Coat
Emergency Repair

Honeywell

Honeywell Firefighting Gloves



HYSAFETY
EURO VI
FIREMAN VI



BSP FIREFIGHTING SUITS
EN Manufactured to NFPA
Eagle I, Eagle II, Century Series
Phenix Tech. Helmets-NFPA



THERMOPROBE- Intrinsically Safe
Thermometers Tank Gauging
Thermometer Stem Thermometer
for Labs and Field Reference



UVEX-Lens

Cleaning Supplies

eyesaline

EYESALINE
Eyewash



BOUTON - Lens Cleaning
Supplies



HARVIK- Firefighting
Boots EN & NFPA



SICOR- Firefighting
Helmets-EN

PGI- Firefighting
Hoods-NFPA



KOLOR KUT

Water Finding Paste-KK01&KKM3
Gas Finding Paste- KK02



MOLYSLIP

Anti-Seize Lubricants Copaslip
High Temp

NEVER-SEEZE

Anti-Seize Lubricants



DRAEGER

SCBA- PSS 3000/5000
Respirators, Gas Detectors
Chemical Protection Suits



KIDDE

Battery Operated Smoke Detector
HSG HOME SAFEGUARD
25-S Detector Tester to NFPA



TEMPEST- PPV BLOWERS

DD-Series- Direct drive

BD-Series- Belt Drive

EB- Electrical and Hazardous Area

FIREFIGHTING HOSES

ARMTEX ARMTEX

BLINDEX BLINDEX

TITAN TITAN



MORSE

Industrial Bandsaws

GARCO

Packing Tools

GOJO

Industrial Hand Cleaners



AMKUS - Hydraulic Rescue Tools



PARATECH- Air Lifting Bags
Rescue Tools, Rescue Struts



VIPER- Firefighting Nozzles

Viper SG3012/SG7515- Adjustable

Rylstatic- New Nozzle Technology

BD3012/BD7515- Adjustable



MSA- Safety Helmets and Wear



Nemesis- Eye Protection

HAZARDOUS AREA FLASHLIGHTS



BRIGHTSTAR- UL DIV1

Lights and Lantern



PELICAN- FM Approved
Lights and Headlamps

MAGLITE- Aluminum Body



DELTA FIRE Foam Equipment

Foam Branch HV225/450

Foam Eductors Z225/450

Mobile Foam DF130



PACIFIC AND FIRE AEC Co., Ltd.



HEAD OFFICE

PACIFIC AND FIRE AEC Co.,Ltd.

51/193 Moo1 Soi Wat-Bangsrimuang Thanam-non Rd.
T.Bangsrimuang A.Muang Nonthaburi 11000 Thailand
Tel : 02-038-5840-41 Fax : 02-886-7585

Customer Service : Fire and Rescue

Mobile Phone : 081-850-0344
E-mail : csfire@pacificandfire.com
Line Id : pacific-fire

Customer Service : Safety And Industrial Tools

Mobile Phone : 081-829-7261
E-mail : customer@eis-pacific.com
Line Id : devcon__pacific

Customer Service : DEVCON Epoxies

Mobile Phone : 081-825-1634
E-mail : csdevcon@pacificandfire.com
Line Id : devcon__pacific



www.pacificandfire.com www.eis-pacific.com